borg& overström

Compact design for flexibility

Hygienic and ergonomic, B4 flourishes in all environments – from boardroom to sports hall. Its compact size, large dispense area for bottles, multiple water options and flexible configuration make it Borg & Overström's most popular mode

Reasons to choose

Ultra-hygienic touch-sensitive control panel High capacity dispense area for bottles and jugs Sealed, hygienic, direct-chill cooling system Floorstanding option comes complete with an internal alarmed waste kit





Distinctive by design.



borg& overström

Borg & Overström Totality®



Driven by a relentless pursuit of excellence, Borg & Overström Totality® is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.

Water system Direct Chill Direct Chill Water options Water options Water options Chilled hygiene, cchnology stems. Hot Sparkling



Configurations Counter-top Or Floorstand

Laboratory certified 99.999% bacteria-reduced Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitizing procedure. The reassurance of hygienically safe appliances is provided by the unique bacteriareducing process, SterizenTM.

Throughput gallons per hour Chilled 9.2/Hot 1.6



Biofilm, limescale and impact resistant epoxy resin panel finish Providing an increased level of hygiene and longevity, Fynil™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.





B4 models Countertop Water Dispense Max power W13"x D18.5"x H16.25" system height consumption Power requirements Chilled, Hot & Ambient Direct Chill 10.75″ 600 Watts 100-115 VAC 50Hz Silver 10.75″ Direct Chill 600 Watts 103550 Chilled, Hot & Sparkling 103546 Chilled temperature 36.8° – 51.5° F Floorstanding W13"x D18.5"xH52.25" Silver Hot temperature 198° F Internal dimension - W11"xD13"xH32.6" Base cabinet 103910



Distinctive by design.



